

RS485 to LoRaWAN Converter

RS485-LN



OVERVIEW:

The Dragino RS485-LN is a RS485 to LoRaWAN Converter. It converts the RS485 signal into LoRaWAN wireless signal which simplify the IoT installation and reduce the installation/maintaining cost.

RS485-LN allows the user to monitor / control RS485 devices and reach extremely long ranges. It provides ultra-long range spread spectrum communication and high interference immunity whilst minimizing current consumption. It targets professional wireless sensor network applications such as irrigation systems, smart metering, smart cities, smartphone detection, building automation, and so on

For data uplink, RS485-LN sends user-defined commands to RS485 devices and get the return from the RS485 devices. RS485-LN will process these returns according to the user-define rule to get the final payload to upload to LoRaWAN server.

For data downlink, RS485-LN runs in LoRaWAN Class C and will forward the commands from LoRaWAN server to RS485 devices.

Features:

- STM32L072CZT6 MCU
- SX1276/78 LoRa Wireless Chip
- LoRaWAN Class C protocol
- Flexible rules to connect different RS485 devices
- Bands: CN470/EU433/KR920/US915
- EU868/AS923/AU915/IN865/RU864
- AT Commands to change parameters
- Support modbus protocol devices
- Uplink on periodically or polling
- Downlink to send RS485 commands

Applications:

- Smart Buildings & Home Automation
- Logistics and Supply Chain Management
- Smart Metering
- Smart Agriculture
- Smart Cities
- Smart Factory

Interfaces:

- RS485 x 1
- Power Input 7~24V

Ordering Info:

- RS485-LN-EU433
- RS485-LN-EU868
- RS485-LN-KR920
- RS485-LN-CN470
- RS485-LN-AS923
- RS485-LN-AU915
- RS485-LN-US915
- RS485-LN-RU864
- RS485-LN-IN865

Dragino Technology Co., Limited

Room 202, Block B, BCT Incubation Bases (BaoChengTai), No.8 CaiYunRoad
LongCheng Street, LongGang District ; Shenzhen 518116,China
Direct: +86 755 86610829 | Fax: +86 755 86647123

WWW.DRAGINO.COM
sales@dragino.com