



PRODUCT SPECIFICATIONS

LoRaWAN™ Sensor Device
MODEL: LS-113G (PM_{2.5})

Version: V1.0



GlobalSat WorldCom Corporation
16F., No. 186, Jian 1st Rd., Zhonghe Dist.,
New Taipei City 23553, Taiwan
Tel: 886.2.8226.3799/ Fax: 886.2.8226.3899
lora@globalsat.com.tw
www.globalsat.com.tw

USGlobalSat Incorporated
14740 Yorba Court, Chino, CA 91710
Tel: 888.323.8720 / Fax: 909.597.8532
sales@usglobalsat.com

Introduction:

LS-113G is designed to measure Particle, Temperature and Humidity by LoRa[®] long-range and low-power wireless connectivity. It is integrated LoRa[®] wireless technology, Laser dust (PM_{2.5}) sensor knowhow and high-performance MCU solution for various IoT markets usage. With calibrated dust (PM_{2.5}) sensor module and compensated Temperature/ Humidity sensor integration, the data is ready for use. It is perfect to detect the dust in the air, like air purifier, air conditioner and air monitor.

Product Features:

- LoRaWAN[™] compliant
- High Receiver Sensitivity and Long Range Solution
- Integrated with calibrated Dust Particles Sensor
 - Range: 0 ~ 500 µg/m³
- Integrated with Compensated Temperature and Humidity Sensor
- Wide range DC power-in, 8 ~ 12 V /or Micro-USB DC power-in, 5V
- Display PM_{2.5} concentration, Temperature and Humidity
- Alarm LED indicator

Specifications

Wireless	
LoRa [®] Module	LoRa Alliance [™] certified module LM-130H1
Sensitivity	-132 dBm @ 980 bps
Tx Power	Up to 100 mW
Standard/ Protocol	Comply with LoRaWAN [™] protocol
LoRa [®] Antenna	External RPSMA Antenna
Frequency	863 ~ 870 MHz (EU) 902 ~ 928 MHz (US) 920 ~ 928 MHz (ROA)
Sensor Operation	
Sensing Element	Dust: Laser light scattering principle Temperature & humidity: CMOS sensor
The unit of measurement	$\mu\text{g}/\text{m}^3$
Response Time	Dust: < 10 sec. Temperature: min. 3 sec. ; max. 30sec. at τ 63% Humidity: < 8 sec. at τ 63%
Accuracy (at 25°C)	Dust: $1 \mu\text{g}/\text{m}^3$ Temperature: $\pm 0.5 \text{ }^\circ\text{C}$ Humidity: $\pm 5 \text{ \%RH}$
Repeatability	Dust: $\pm 10\%$ @ $100 \sim 500 \mu\text{g}/\text{m}^3$, $\pm 10 \mu\text{g}/\text{m}^3$ @ $0 \sim 100 \mu\text{g}/\text{m}^3$ Temperature: $\pm 0.3 \text{ }^\circ\text{C}$ Humidity: $\pm 0.3 \text{ \%RH}$
Zero Drift	Temperature: < $0.04 \text{ }^\circ\text{C}/\text{yr.}$ Humidity: < $0.5 \text{ \%RH}/\text{yr.}$
Measurement Range*	Dust: $0 \sim 500 \mu\text{g}/\text{m}^3$ Temperature: $-10 \sim +60 \text{ }^\circ\text{C}$ Humidity: $0 \sim 95 \text{ \%RH}$
System Operation	
Temperature	$-10 \sim +60 \text{ }^\circ\text{C}$
Humidity	$0 \sim 95\%RH$, Non-condensing
Storage Temperature	$-10 \sim +60 \text{ }^\circ\text{C}$
Warm-up Time	$\leq 1 \text{ min.}$ (at full specs $\leq 15 \text{ mins.}$)
LED Indicator	Red LED x 2 (by threshold setting, default are $35 \mu\text{g}/\text{m}^3$ and

Specifications

	55 µg/m ³)
Power Supply	Wide range DC power-in, 8 ~ 12 V or Micro-USB DC 5 V
Installation	Wall-mount
Dimension (mm)	Wall-mount: 117.3(H) x 84.1(W) x 28.1(D) ± 0.1 mm
Weight	132 ± 0.2 g
Case Material	PC
Accessory	
Standard	LoRa [®] Antenna x 1
Optional	Sensor Programmable Cable (Micro USB to UART)

LED Indicators

Please refer to AT Commands for LS-11x to adjust the alarm defaults.

Criteria	LED1	LED2
Low Criterion (Default: 35 µg/m ³)	Glowing	Dark
High Criterion (Default: 55 µg/m ³)	Glowing	Glowing