

# LoRaWAN® BK-G Pulse Reader CM3061 Payload Structures

This document contains only payload structure definitions for firmware versions 2.3.x, the rest of the information can be found in [CM3061 Datasheet](#).

## Table of Contents

- 1 LoRaWAN Payloads
  - 1.1 LoRaWAN Timed Payload
    - 1.1.1 `usage_packet` and `usage_with_status_packet`
  - 1.2 LoRaWAN Configuration Payloads
    - 1.2.1 `general_configuration_packet`
    - 1.2.2 `location_configuration_packet`
  - 1.3 LoRaWAN Command Payloads
    - 1.3.1 `general_configuration_request` and `location_configuration_request`
    - 1.3.2 `local_time_request` and `enter_dfu_command`
    - 1.3.3 `local_time_response`
    - 1.3.4 `faulty_downlink_packet`
  - 1.4 LoRaWAN Other Payloads
    - 1.4.1 `boot_packet`
    - 1.4.2 `shutdown_packet`
- 2 wM-Bus Payload
- 3 Annex: Understanding Payload Structures
  - 3.1 Example Payload Structure
  - 3.2 Payload Structure Columns Explanation

# 1 LoRaWAN Payloads

## 1.1 LoRaWAN Timed Payload

### 1.1.1 *usage\_packet* and *usage\_with\_status\_packet*

*usage\_packet* and *usage\_with\_status\_packet* are the only regular payloads, containing everything needed for billing purposes. They are essentially the same packet whereas *usage\_with\_status\_packet* contains extra block (with *battery\_*, *temperature\_*, *radio\_* and *meter\_serial* parameters). Inclusion of this extra block depends on *device\_status\_sent* bit.

Example A *usage\_packet* (unconfirmed packet, without device status, sent frequently) from fPort 25:

04 C0 00 14 43 3F254E00 01

Example B *usage\_with\_status\_packet* (confirmed packet, with device status, sent at midnight and noon) from fPort 25:

04 C0 00 84 43 3F254E00 752B 03 6B D1 16 4A 33 7C 44983938

Byte	Type	Example	Parameter	Details	Example Value																												
0	uint8	0x04	<i>_packet_type</i>	0x04 - <i>usage_packet</i>	<i>usage_packet</i>																												
1	bits8	0xC0	<i>active_alerts</i>	<table border="1"> <thead> <tr> <th>Bit</th><th>Parameter</th><th>Type</th><th>Example</th></tr> </thead> <tbody> <tr> <td>0-2</td><td>RFU</td><td></td><td>b000</td></tr> <tr> <td>3</td><td><i>tamper_pending</i></td><td>pending flag</td><td>0</td></tr> <tr> <td>4</td><td>RFU</td><td></td><td>0</td></tr> <tr> <td>5</td><td><i>battery</i></td><td>instant value</td><td>0</td></tr> <tr> <td>6</td><td><i>no_usage</i></td><td>instant value</td><td>1</td></tr> <tr> <td>7</td><td><i>any_alert_active</i></td><td>instant value</td><td>1</td></tr> </tbody> </table> <p>example: [<i>no_usage</i>]  example: [<i>backflow_pending, no_usage</i>]</p> <p>Pending flag means that alert state is kept pending until next confirmed <i>usage_packet</i>. The pending flags can remain pending for hours even though alert's instant value is already off. <i>any_alert_active_now</i> indicates if instant value of any pending alert is on.</p>	Bit	Parameter	Type	Example	0-2	RFU		b000	3	<i>tamper_pending</i>	pending flag	0	4	RFU		0	5	<i>battery</i>	instant value	0	6	<i>no_usage</i>	instant value	1	7	<i>any_alert_active</i>	instant value	1	
Bit	Parameter	Type	Example																														
0-2	RFU		b000																														
3	<i>tamper_pending</i>	pending flag	0																														
4	RFU		0																														
5	<i>battery</i>	instant value	0																														
6	<i>no_usage</i>	instant value	1																														
7	<i>any_alert_active</i>	instant value	1																														
2	uint8	0x00	RFU																														
3	bits8	0x14 / 0x94	[ <i>meter</i> ]	<table border="1"> <thead> <tr> <th>Bit</th><th>Parameter</th><th>Value</th><th>Example Value A / B</th></tr> </thead> <tbody> <tr> <td>0-2</td><td><i>meter_multiplier</i></td><td>3 = 0.001 (default) 4 = 0.01 5 = 0.1 6 = 1 7 = 10</td><td>b100 = 0x04 = 4 <i>meter_multiplier</i> = 0.01</td></tr> <tr> <td>3-4</td><td><i>meter_medium</i></td><td>2 - <i>gas</i></td><td>b10 - <i>gas</i></td></tr> <tr> <td>5-6</td><td><i>meter_unit</i></td><td>2 - ft3</td><td>b00 -</td></tr> <tr> <td>7</td><td><i>privacy_mode_active</i></td><td></td><td>b0 / b1</td></tr> </tbody> </table>	Bit	Parameter	Value	Example Value A / B	0-2	<i>meter_multiplier</i>	3 = 0.001 (default) 4 = 0.01 5 = 0.1 6 = 1 7 = 10	b100 = 0x04 = 4 <i>meter_multiplier</i> = 0.01	3-4	<i>meter_medium</i>	2 - <i>gas</i>	b10 - <i>gas</i>	5-6	<i>meter_unit</i>	2 - ft3	b00 -	7	<i>privacy_mode_active</i>		b0 / b1									
Bit	Parameter	Value	Example Value A / B																														
0-2	<i>meter_multiplier</i>	3 = 0.001 (default) 4 = 0.01 5 = 0.1 6 = 1 7 = 10	b100 = 0x04 = 4 <i>meter_multiplier</i> = 0.01																														
3-4	<i>meter_medium</i>	2 - <i>gas</i>	b10 - <i>gas</i>																														
5-6	<i>meter_unit</i>	2 - ft3	b00 -																														
7	<i>privacy_mode_active</i>		b0 / b1																														
4	uint8	0x43	<i>meter_actuality_duration_minutes</i> (for <i>volume</i> )	0-59 - <i>minutes_ago</i> (if <60) 64-155 - <i>quarter_hours_ago</i> (1 h - 23 h 45 min) (if <156) 157-198 - <i>days_ago</i> (1 day - 42 days) (if <200) 255 - n/a examples: 53 → 53 (minutes), 67 → 67-60 = 7 * 15 (min) = 1:45, 161 → 161 - 156 = 5 (days)	0x43 = 67 67 - 60 * 15 (min) = 7 * 15 (min) = 105 (min) = 1:45																												
5	uint32	0x3F	<i>meter_accumulated_volume_m3</i>	convert: * <i>meter_multiplier</i>	0x004E253F = 5121343																												
6		0x25	<i>meter_accumulated_volume_gal</i>	<i>0x7FFFFFFF - not available</i>	5121343 * <i>meter_multiplier</i> =																												
7		0x4E	<i>meter_accumulated_volume_ft3</i>		5121343 * 0.01 =																												
8		0x00			51213.43 (m³)																												
r0	bits16	0x75	<i>meter_readout_date</i>	when: <i>metering_info.privacy_mode_active</i> converting: identical to M-Bus Type E (Compound CP16)																													
r1		0x2B	(key-date for <i>meter_accumulated_volume_L</i> )	<table border="1"> <thead> <tr> <th>Bit</th><th>Parameter</th><th>Value</th><th>Example B</th></tr> </thead> <tbody> <tr> <td>0-4</td><td><i>day</i></td><td>1-31</td><td>b10101 = 0x15 = 21</td></tr> <tr> <td>5-7</td><td><i>year_lower</i></td><td></td><td>b011 = 0x03 = 3</td></tr> <tr> <td>8-11</td><td><i>month</i></td><td>1-12</td><td>b1011 = 0x0B = 11</td></tr> <tr> <td>12-15</td><td><i>year_upper</i></td><td></td><td>b0010 = 0x02 = 2</td></tr> </tbody> </table> <p><i>year</i> = <i>year_lower</i> + 8 * <i>year_upper</i> = 3 + 8 * 2 = 3 + 16 = 19  example: 0x75 0x2B → 2019-11-21</p>	Bit	Parameter	Value	Example B	0-4	<i>day</i>	1-31	b10101 = 0x15 = 21	5-7	<i>year_lower</i>		b011 = 0x03 = 3	8-11	<i>month</i>	1-12	b1011 = 0x0B = 11	12-15	<i>year_upper</i>		b0010 = 0x02 = 2									
Bit	Parameter	Value	Example B																														
0-4	<i>day</i>	1-31	b10101 = 0x15 = 21																														
5-7	<i>year_lower</i>		b011 = 0x03 = 3																														
8-11	<i>month</i>	1-12	b1011 = 0x0B = 11																														
12-15	<i>year_upper</i>		b0010 = 0x02 = 2																														

	r0	bits8	0x01 / 0x03	[general_parameters]	<table border="1"> <thead> <tr> <th>Bit</th><th>Parameter</th><th>Value</th><th>Example A / B</th></tr> </thead> <tbody> <tr> <td>0</td><td><i>app_connected_within_a_day</i></td><td>0 - false, 1 - true</td><td>1 / 1</td></tr> <tr> <td>1</td><td><i>device_status_sent</i></td><td>0 - not_sent 1 - sent</td><td>0 / 1</td></tr> <tr> <td>3-5</td><td>RFU <i>redundant_count</i></td><td>0 - not_sent 1 - 3</td><td>0b000</td></tr> <tr> <td>6-7</td><td>RFU <i>redundant_interval</i></td><td>0 - 15_min 1 - 1_h 2 - 6_h 3 - 24_h</td><td>0b00</td></tr> </tbody> </table>	Bit	Parameter	Value	Example A / B	0	<i>app_connected_within_a_day</i>	0 - false, 1 - true	1 / 1	1	<i>device_status_sent</i>	0 - not_sent 1 - sent	0 / 1	3-5	RFU <i>redundant_count</i>	0 - not_sent 1 - 3	0b000	6-7	RFU <i>redundant_interval</i>	0 - 15_min 1 - 1_h 2 - 6_h 3 - 24_h	0b00
Bit	Parameter	Value	Example A / B																						
0	<i>app_connected_within_a_day</i>	0 - false, 1 - true	1 / 1																						
1	<i>device_status_sent</i>	0 - not_sent 1 - sent	0 / 1																						
3-5	RFU <i>redundant_count</i>	0 - not_sent 1 - 3	0b000																						
6-7	RFU <i>redundant_interval</i>	0 - 15_min 1 - 1_h 2 - 6_h 3 - 24_h	0b00																						
r0	uint8	0x6B		<i>battery_remaining_years</i>	when: <i>general_parameters.device_status_sent</i> convert: /12.0 0x6B = 107 (months) ≈ 8.9 (years)																				
r1	uint8	0xD1		<i>battery_voltage_V</i>	when: <i>general_parameters.device_status_sent</i> convert: (l100) + 1.5 0xD1 = 209 209 / 100 + 1.5 = 3.59 (V)																				
r2	int8	0x16		<i>temperature_C</i>	when: <i>general_parameters.device_status_sent</i> formatter: %s%s 0x16 = 22																				
r3	bits8	0x4A		[temperature]	<table border="1"> <thead> <tr> <th>Bit</th><th>Parameter</th><th>Example Value</th></tr> </thead> <tbody> <tr> <td>0-3</td><td><i>temperature_min_C</i> (min_offset) convert: *-2 + <i>temperature_C</i></td><td>0xA = 10 10 * -2 + <i>temperature_C</i> = 10 * -2 + 22 = -20 + 22 = 2</td></tr> <tr> <td>4-7</td><td><i>temperature_max_C</i> (max_offset) convert: *2 + <i>temperature_C</i></td><td>0x4 = 4 4 * 2 + <i>temperature_C</i> = 4 * 2 + 22 = 8 + 22 = 30</td></tr> </tbody> </table> <p>note: extremes are reset with each <i>status_packet</i>.</p>	Bit	Parameter	Example Value	0-3	<i>temperature_min_C</i> (min_offset) convert: *-2 + <i>temperature_C</i>	0xA = 10 10 * -2 + <i>temperature_C</i> = 10 * -2 + 22 = -20 + 22 = 2	4-7	<i>temperature_max_C</i> (max_offset) convert: *2 + <i>temperature_C</i>	0x4 = 4 4 * 2 + <i>temperature_C</i> = 4 * 2 + 22 = 8 + 22 = 30											
Bit	Parameter	Example Value																							
0-3	<i>temperature_min_C</i> (min_offset) convert: *-2 + <i>temperature_C</i>	0xA = 10 10 * -2 + <i>temperature_C</i> = 10 * -2 + 22 = -20 + 22 = 2																							
4-7	<i>temperature_max_C</i> (max_offset) convert: *2 + <i>temperature_C</i>	0x4 = 4 4 * 2 + <i>temperature_C</i> = 4 * 2 + 22 = 8 + 22 = 30																							
r4	uint8	0x33		<i>radio_downlink_rssi_dBm</i>	when: <i>general_parameters.device_status_sent</i> convert: *-1 0x33 = 51 51 * -1 = -51 (dBm)																				
r5	bits8	0x7C		[radio]	<table border="1"> <thead> <tr> <th>Bit</th><th>Parameter</th><th>Example Value</th></tr> </thead> <tbody> <tr> <td>0-3</td><td><i>radio_downlink_snr_dB</i> (signal to noise ratio) convert: *2 - 20</td><td>0xC = 12 12 * 2 - 20 = 24 - 20 = 4 (dB)</td></tr> <tr> <td>4-7</td><td><i>radio_uplink_power_dBm</i> convert: *2</td><td>0x7 = 7 7 * 2 = 14 (dBm)</td></tr> </tbody> </table> <p>example: 0x27 → <i>radio_downlink_snr</i> = -6 dB and <i>radio_uplink_pwr</i> = 4 dBm</p>	Bit	Parameter	Example Value	0-3	<i>radio_downlink_snr_dB</i> (signal to noise ratio) convert: *2 - 20	0xC = 12 12 * 2 - 20 = 24 - 20 = 4 (dB)	4-7	<i>radio_uplink_power_dBm</i> convert: *2	0x7 = 7 7 * 2 = 14 (dBm)											
Bit	Parameter	Example Value																							
0-3	<i>radio_downlink_snr_dB</i> (signal to noise ratio) convert: *2 - 20	0xC = 12 12 * 2 - 20 = 24 - 20 = 4 (dB)																							
4-7	<i>radio_uplink_power_dBm</i> convert: *2	0x7 = 7 7 * 2 = 14 (dBm)																							
r6	uint32	0x44		<i>meter_serial</i> (sn of meter)	when: <i>general_parameters.device_status_sent</i> format: hex (BCD - binary coded decimal)  0xFFFFFFFF - <i>not_available</i>  0x44 0x98 0x39 0x38 → 38399844																				
r7		0x98																							
r8		0x39																							
r9		0x38																							

## 1.2 LoRaWAN Configuration Payloads

### 1.2.1 general\_configuration\_packet

Example payload

20 1F0C 17 02 44983938 14 DEBB2A1300000000 0700 01

Byte	Type	Example	Parameter	Details	Example Value																								
0	uint8	0x20	_packet_type	0x20 - general_configuration_packet	general_configuration_packet																								
1	bits8	0x1F	configured_parameters	<table border="1"> <thead> <tr> <th>Bit</th><th>Parameter</th><th>Example</th></tr> </thead> <tbody> <tr> <td>0</td><td>radio_lorawan_profile_sent</td><td>1</td></tr> <tr> <td>1</td><td>radio_wmbus_profile_sent</td><td>1</td></tr> <tr> <td>2</td><td>meter_serial_sent</td><td>1</td></tr> <tr> <td>3</td><td>meter_unit_medium_multiplier_sent</td><td>1</td></tr> <tr> <td>4</td><td>meter_accumulated_volume_sent*</td><td>1</td></tr> <tr> <td>5</td><td>meter_accumulated_volume_offset_sent*</td><td>0</td></tr> <tr> <td>6-7</td><td>RFU</td><td>b00</td></tr> </tbody> </table>	Bit	Parameter	Example	0	radio_lorawan_profile_sent	1	1	radio_wmbus_profile_sent	1	2	meter_serial_sent	1	3	meter_unit_medium_multiplier_sent	1	4	meter_accumulated_volume_sent*	1	5	meter_accumulated_volume_offset_sent*	0	6-7	RFU	b00	*These can not be configured together, meter_accumulated_volume_offset_L will be ignored
Bit	Parameter	Example																											
0	radio_lorawan_profile_sent	1																											
1	radio_wmbus_profile_sent	1																											
2	meter_serial_sent	1																											
3	meter_unit_medium_multiplier_sent	1																											
4	meter_accumulated_volume_sent*	1																											
5	meter_accumulated_volume_offset_sent*	0																											
6-7	RFU	b00																											
2	bits8	0x0C	configured_parameters	<table border="1"> <thead> <tr> <th>Bit</th><th>Parameter</th><th>Example</th></tr> </thead> <tbody> <tr> <td>0-1</td><td>RFU</td><td>b00</td></tr> <tr> <td>2</td><td>alert_no_usage_sent</td><td>1</td></tr> <tr> <td>3</td><td>alert_tamper_sent</td><td>1</td></tr> <tr> <td>4-7</td><td>RFU</td><td>b0000</td></tr> </tbody> </table>	Bit	Parameter	Example	0-1	RFU	b00	2	alert_no_usage_sent	1	3	alert_tamper_sent	1	4-7	RFU	b0000										
Bit	Parameter	Example																											
0-1	RFU	b00																											
2	alert_no_usage_sent	1																											
3	alert_tamper_sent	1																											
4-7	RFU	b0000																											
r0	uint8	0x17	radio_lorawan_profile	when: configured_parameters. radio_lorawan_profile_sent  0x00 - lorawan_disabled 0x01 - lorawan_24_h_privacy 0x02 - lorawan_24_h 0x03 - lorawan_12_h 0x07 - lorawan_1_h_static 0x08 - lorawan_15_min_static 0x17 - lorawan_1_h_dynamic 0x18 - lorawan_15_min_dynamic	lorawan_1_h_dynamic																								
r0	uint8	0x02	radio_wmbus_profile	when: configured_parameters.radio_wmbus_profile_sent  0x00 - wmbus_disabled 0x01 - wmbus_privacy 0x02 - wmbus_driveby 0x03 - wmbus_fixnet	wmbus_driveby																								
r0	uint32	0x44	meter_serial (sn of meter)	when: configured_parameters.meter_serial_sent type: hex  0xFFFFFFFF - not_set	0x44 0x98 0x39 0x38 → 0x38399844 → 38399844																								
r1		0x98																											
r2		0x39																											
r3		0x38																											
r0	uint8	0x14	[meter_mode]	when: configured_parameters.meter_unit_medium_multiplier_sent	<table border="1"> <thead> <tr> <th>Bit</th><th>Parameter</th><th>Value</th><th>Example</th></tr> </thead> <tbody> <tr> <td>0-2</td><td>meter_multiplier</td><td>3 - 0.001 (default) 4 - 0.01 5 - 0.1 6 - 1 7 - 10</td><td>b100 = 0x04 = 4 meter_multiplier = 0.01</td></tr> <tr> <td>3-4</td><td>meter_medium</td><td>2 - gas</td><td>b10 - gas</td></tr> <tr> <td>5-6</td><td>meter_unit</td><td>2 - ft³ (ft³)</td><td>b00 -</td></tr> <tr> <td>7</td><td>RFU</td><td></td><td>0</td></tr> </tbody> </table>	Bit	Parameter	Value	Example	0-2	meter_multiplier	3 - 0.001 (default) 4 - 0.01 5 - 0.1 6 - 1 7 - 10	b100 = 0x04 = 4 meter_multiplier = 0.01	3-4	meter_medium	2 - gas	b10 - gas	5-6	meter_unit	2 - ft³ (ft³)	b00 -	7	RFU		0				
Bit	Parameter	Value	Example																										
0-2	meter_multiplier	3 - 0.001 (default) 4 - 0.01 5 - 0.1 6 - 1 7 - 10	b100 = 0x04 = 4 meter_multiplier = 0.01																										
3-4	meter_medium	2 - gas	b10 - gas																										
5-6	meter_unit	2 - ft³ (ft³)	b00 -																										
7	RFU		0																										
r0	uint64	0xDE	meter_accumulated_volume_m3 meter_accumulated_volume_gal meter_accumulated_volume_ft3	when: configured_parameters. meter_accumulated_volume_sent	0x00000000132ABBDE = 321567710  321567710 / 1000 = 321567.710(m³)																								
r1		0xBB																											

r2		0x2A	(absolute reading)	note: last decimal places will be floored with larger <i>meter_multiplier</i> convert: /1000.0	
r3		0x13			
r4		0x00			
r5		0x00			
r6		0x00			
r7		0x00			
r0	int32	0xBE	<i>meter_accumulated_volume_offset_m3</i>	when: <i>configured_parameters.meter_accumulated_volume_offset_gal</i>	0xFFFFE7BE = -6210
r1		0xE7	<i>meter_accumulated_volume_offset_gal</i>	note: last decimal places will be floored with larger <i>meter_multiplier</i> convert: /1000.0	-6210 / 1000 = -6.210 (m <sup>3</sup> )
r2		0xFF	<i>meter_accumulated_volume_offset_ft3</i>		
r3		0xFF	(relative reading)		
r0	uint16	0x07	<i>alert_no_usage_interval_days</i>	when: <i>configured_parameters.alert_no_usage_sent</i>	0x0007 = 7 (days)
r1		0x00		min: 1, max: 400  0 - disabled	
r0	uint8	0x01	<i>alert_tamper_enabled</i>	when: <i>configured_parameters.alert_tamper_sent</i>	true

### 1.2.2 *location\_configuration\_packet*

In EU868 region DR0 has maximum payload length of 51 bytes which is less than maximum data in *location\_configuration\_packet*. Therefore the packet may be sent or received in two parts, the longest address field and all the rest of the fields. *address*, *id\_customer* and *id\_location* all contain utf-8 string where single unicode symbol can take several bytes.

Example payload to/from fPort 50:

21 1F AC5E6D23 0017C10E F4 12 c396c3b662696b75205374722e2032 2d3136 10 323656303030303030303337313734 05 3132414236

Byte	Type	Example	Parameter	Details	Example Value																					
0	uint8	0x21	<i>_packet_type</i>	0x21 - <i>location_configuration_packet</i>	<i>location_configuration_packet</i>																					
1	bits8	0x1F	<i>configured_parameters</i>	<table border="1"> <thead> <tr> <th>Bit</th> <th>Parameter</th> <th>Example</th> </tr> </thead> <tbody> <tr> <td>0</td><td><i>gps_position_sent</i></td><td>b1</td></tr> <tr> <td>1</td><td><i>time_zone_sent</i></td><td>b1</td></tr> <tr> <td>2</td><td><i>address_sent</i></td><td>b1</td></tr> <tr> <td>3</td><td><i>id_customer_sent</i></td><td>b1</td></tr> <tr> <td>4</td><td><i>id_location_sent</i></td><td>b1</td></tr> <tr> <td>5-7</td><td>RFU</td><td>b000</td></tr> </tbody> </table>	Bit	Parameter	Example	0	<i>gps_position_sent</i>	b1	1	<i>time_zone_sent</i>	b1	2	<i>address_sent</i>	b1	3	<i>id_customer_sent</i>	b1	4	<i>id_location_sent</i>	b1	5-7	RFU	b000	
Bit	Parameter	Example																								
0	<i>gps_position_sent</i>	b1																								
1	<i>time_zone_sent</i>	b1																								
2	<i>address_sent</i>	b1																								
3	<i>id_customer_sent</i>	b1																								
4	<i>id_location_sent</i>	b1																								
5-7	RFU	b000																								
r0	int32	0xAC	<i>gps_position_latitude_deg</i>	when: <i>configured_parameters.gps_position_sent</i> converter: /10e7	0x236D5EAC = 594370220																					
r1		0x5E		0x7FFFFFFF - <i>not_configured</i>	594370220 / 10000000 = 59.4370220 = 59°26'13.3"N																					
r2		0x6D																								
r3		0x23																								
r4	int32	0x00	<i>gps_position_longitude_deg</i>		0x0EC11700 = 247535360																					
r5		0x17			247535360 / 10000000 = 24.7535360 = 24°45'12.7"E																					
r6		0xC1																								
r7		0x0E																								
r0	int8	0xF4	<i>time_zone_h</i> (winter time recommended)	when: <i>configured_parameters.time_zone_sent</i> converter: /4 min: -12 h max: 14 h	0xF4 = -12 -12 / 4 = -3.0 (h) = UTC-3																					
r0	uint8	0x12	<i>address_len</i> (length in bytes)	when: <i>configured_parameters.address_sent</i> values: 1 - 38  0x00 - <i>not_configured</i>	0x12 = 18 (bytes)																					
r1	string	0xc3	<i>address</i>	when: <i>address_len</i> not 0 length: <i>address_len</i> type: utf-8 string note: does not end with '\0'	0xc3 0x96 0xc3 0xb6 0x62 0x69 0xb6 0x75 0x20 0x53 0x74 0x72 0x2e 0x20 0x32 0x2d 0x31 0x36 → "Ööbiku Str. 2-16"																					
r2		0x96																								
...		0xc3 0xb6																								
...		0x62 0x69																								
		0x6b 0x75																								
		0x20 0x53																								
		0x74 0x72																								

r0+ _address_len		0x2e 0x20 0x32 0x2d 0x31 0x36			
r0	uint8	0x10	<i>id_customer_len</i> (length in bytes)	when: <i>configured_parameters.id_customer_sent</i> values: 1-16  0x00 - <i>not_configured</i>	0x10 = 16 (bytes)
r1	string	0x32	<i>id_customer</i>	when: <i>id_customer_len</i> not 0 length: <i>id_customer_len</i> type: utf-8 string note: string does not end with '\0'	0x32 0x36 0x56 0x30 0x30 0x30 0x30 0x30 0x30 0x30 0x30 0x33 0x37 0x31 0x37 0x34 → "26V000000037174"
r2		0x36			
...		0x56 0x30			
...		0x30 0x30			
r0+ _id_customer_len		0x30 0x30			
		0x30 0x33			
		0x37 0x31			
		0x37 0x34			
r0	uint8	0x05	<i>id_location_len</i> (length in bytes)	when: <i>configured_parameters.id_location_sent</i> values 1-16  0x00 - <i>not_configured</i>	0x05 = 5 (bytes)
r1	string	0x31	<i>id_location</i>	when: <i>id_location_len</i> not 0 length: <i>id_location_len</i> type: utf-8 string note: string does not end with '\0'	0x31 0x32 0x41 0x42 0x36 → "12AB6"
r2		0x32			
...		0x41			
...		0x42			
r0+ _id_location_len		0x36			

## 1.3 LoRaWAN Command Payloads

There are two types of commands: configuration requests (fPort 49) and commands (fPort 60).

### 1.3.1 *general\_configuration\_request* and *location\_configuration\_request*

The response is sent to same port in the same format as configuration message for this package.

Example payload to fPort 49: 20

Byte	Type	Example	Parameter	Details	Example Value
0	uint8	0x20	_packet_type	0x20 - <i>general_configuration_request</i> 0x21 - <i>location_configuration_request</i>	<i>general_configuration_request</i>

### 1.3.2 *local\_time\_request* and *enter\_dfu\_command*

*enter\_dfu\_command* response is *shutdown\_packet* with reason *enter\_dfu*, sent only if duty allows it. *local\_time\_request* is responded with *local\_time\_response*.

Example payload to fPort 60: FF

Byte	Type	Example	Parameter	Details	Example Value
0	uint8	0xFF	command_type	0x03 - <i>local_time_request</i> 0xFF - <i>enter_dfu_command</i>	<i>enter_dfu_command</i>

### 1.3.3 *local\_time\_response*

Example payload from fPort 60: 03 34546A5F

Byte	Type	Example	Parameter	Details	Example Value
0	uint8	0x03	_packet_type	0x03 - <i>local_time_response</i>	<i>local_time_response</i>
1	uint32_t	0x34	device_local_time_s device_local_time_formatted (CM3061 local time)	note: treat as unix epoch in local time	0x5F6A5434 = 1600803892 → 2020-09-22T19:44:52Z (local time)
2		0x54			
3		0x6A			
4		0x5F			

### 1.3.4 *faulty\_downlink\_packet*

If any configuration or command packet parsing fails, an error code is sent back.

Example payload from fPort 99: 13 32 05

Byte	Type	Example	Parameter	Details	Example Value
0	uint8	0x13	_packet_type	0x13 - <i>faulty_downlink_packet</i>	<i>faulty_downlink_packet</i>
1	uint8	0x32	packet_fport	original fPort where the invalid packet arrived	0x32 = 50 (fPort)
2	uint8	0x05	packet_error_reason	0x00 - n/a 0x01 - n/a 0x02 - unknown_fport 0x03 - packet_size_short 0x04 - packet_size_long 0x05 - value_error 0x06 - protocol_parse_error 0x07 - reserved_flag_set 0x08 - invalid_flag_combination unsupported_header internal_error	<i>value_error</i>

## 1.4 LoRaWAN Other Payloads

---

### 1.4.1 boot\_packet

Sent after boot and every rejoin.

Example payload from fPort 99: 00 2B001650 020312 80 A0 FF 0000 371100

Byte	Type	Example	Parameter	Details	Example Value																								
0	uint8	0x00	_packet_type	0x00 - boot_packet	boot_packet																								
1	uint32	0x2B	device_serial (sn of CM3061)	formatting: hex	0x5016002B → 5016002B																								
2		0x00																											
3		0x16																											
4		0x50																											
5	uint8	0x02	device_firmware_version	hardware	0x02 0x03 0x12 → 2.3.18																								
6	uint8	0x03		major																									
7	uint8	0x12		minor																									
8	bits8	0x80	wakeup_reason	note: all fields are cleared if general_info: lorawan_rejoin <table border="1"> <thead> <tr> <th>Bit</th> <th>Parameter</th> <th>Example</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>RFU</td> <td>0</td> </tr> <tr> <td>1</td> <td>watchdog_reset</td> <td>0</td> </tr> <tr> <td>2</td> <td>soft_reset (e.g. from dfu_mode)</td> <td>0</td> </tr> <tr> <td>3</td> <td>RFU</td> <td>0</td> </tr> <tr> <td>4</td> <td>magnet_wakeup</td> <td>0</td> </tr> <tr> <td>5-6</td> <td>RFU</td> <td>b00</td> </tr> <tr> <td>7</td> <td>nfc_wakeup</td> <td>1</td> </tr> </tbody> </table> example: [nfc_wakeup]	Bit	Parameter	Example	0	RFU	0	1	watchdog_reset	0	2	soft_reset (e.g. from dfu_mode)	0	3	RFU	0	4	magnet_wakeup	0	5-6	RFU	b00	7	nfc_wakeup	1	
Bit	Parameter	Example																											
0	RFU	0																											
1	watchdog_reset	0																											
2	soft_reset (e.g. from dfu_mode)	0																											
3	RFU	0																											
4	magnet_wakeup	0																											
5-6	RFU	b00																											
7	nfc_wakeup	1																											
9	bits8	0xA0	general_info	<table border="1"> <thead> <tr> <th>Bit</th> <th>Parameter</th> <th>Example</th> </tr> </thead> <tbody> <tr> <td>0-4</td> <td>RFU</td> <td>b0000</td> </tr> <tr> <td>5</td> <td>wakeup_from_dfu</td> <td>1</td> </tr> <tr> <td>6</td> <td>lorawan_rejoin</td> <td>0</td> </tr> <tr> <td>7</td> <td>configuration_restored</td> <td>1</td> </tr> </tbody> </table>	Bit	Parameter	Example	0-4	RFU	b0000	5	wakeup_from_dfu	1	6	lorawan_rejoin	0	7	configuration_restored	1										
Bit	Parameter	Example																											
0-4	RFU	b0000																											
5	wakeup_from_dfu	1																											
6	lorawan_rejoin	0																											
7	configuration_restored	1																											
10	uint8	0xFF	hardware_configuration	0x20 - BK_G 0xFF - n/a (will never occur)	n/a																								
11	uint16	0x00	RFU																										
12		0x00																											
13	uint24	0x37	device_uptime_accumulated_days	convert: /24.0  0x001137 = 4407 (h) 4407 / 24.0 ≈ 183,6 (days)																									
14		0x11																											
15		0x00																											

## 1.4.2 shutdown\_packet

If LoRaWAN is not duty-limited, shutdown packet is sent out to indicate the shutdown reason

Example payload from fPort 99:

01 33 04C00054 433F254E00752B036BD1164A337C44983938

Byte	Type	Example	Parameter	Details	Example Value
0	uint8	0x01	_packet_type	0x01 - shutdown_packet	shutdown_packet
1	uint8	0x33	_shutdown_reason	0x31 - magnet_shutdown 0x32 - enter_dfu 0x33 - app_shutdown 0x34 - switch_to_wmbus	app_shutdown
2	rest of bytes	0x04	[usage_with_status_packet]	comment: full usage_with_status_packet payload structure	see usage_with_status_packet example
3		0xC0			
4		0x00			
...		...			
...		...			

## 2 wM-Bus Payload

Example payload:

2F2F 0374 201C00 0414 AE0A8D01 4414 180A8D01 426C 752B 02FD74 BD0C 0F01 8088

Byte	Type	Example	Parameter	Example Value																											
0	uint8	0x2F	<i>aes_verification</i>																												
1	uint8	0x2F	<i>aes_verification</i>																												
2	uint8	0x03	<i>meter_actuality_duration_s</i> - DIF (int24)																												
3	uint8	0x74	<i>meter_actuality_duration_s</i> - VIF (sec)																												
4	int24	0x20	<i>meter_actuality_duration_s</i>	0x001C20 = 7200 (sec)																											
5		0x1C	(for <i>meter_accumulated_volume_L</i> )																												
6		0x00																													
7	uint8	0x04	<i>meter_accumulated_volume_L</i> - DIF 0x04 (int32)																												
8	uint8	0x14 (0x13...0x17)	<i>meter_accumulated_volume_L</i> - VIF	0x14, <i>meter_multiplier</i> = 10																											
9	int32	0xAE	<i>meter_accumulated_volume_L</i> note: not sent if <i>privacy_mode_active</i>	0x018D0AAE = 26020526 26020526 * <i>meter_multiplier</i> = 26020526 * 10 = 260205260 (L)																											
10		0x0A																													
11		0x8D																													
12		0x01																													
13	uint8	0x44	<i>meter_key_date_accumulated_volume_L</i> - DIF (int32)																												
14	uint8	0x14 (0x13...0x17)	<i>meter_key_date_accumulated_volume_L</i> - VIF	0x14, <i>meter_multiplier</i> = 10																											
15	int32	0x18	<i>meter_key_date_accumulated_volume_L</i>	0x018D0A18 = 26020376 26020376 * <i>meter_multiplier</i> = 26020376 * 10 = 260203760 (L)																											
16		0x0A																													
17		0x8D																													
18		0x01																													
19	uint8	0x42	<i>meter_key_date</i> - DIF (int16)																												
20	uint8	0x6C	<i>meter_key_date</i> - VIF																												
21	int16	0x75	<i>meter_key_date</i> (for <i>meter_key_date_accumulated_volume_L</i> )	0x75 0x2B → 21.11.2019																											
22		0x2B																													
23	uint8	0x02	<i>remaining_battery_days</i> - DIF (int16)																												
24	uint8	0xFD	<i>remaining_battery_days</i> - VIF																												
25	uint8	0x74	<i>remaining_battery_days</i> - VIFE																												
26	int16	0xBD	<i>remaining_battery_days</i>	0x0CBD = 3261 (days)																											
27		0x0C																													
28	uint8	0x0F	<i>manufacturer_specific</i> - DIF																												
29	uint8	0x01	<i>manufacturer_specific</i> - Type (decimal 1)																												
30	bits8	0x80	<i>manufacturer_specific</i>																												
			<table border="1"> <thead> <tr> <th>Bit</th><th>Parameter</th><th>Example</th></tr> </thead> <tbody> <tr> <td>0</td><td><i>alert_tamper</i></td><td>0</td></tr> <tr> <td>1</td><td>RFU</td><td>0</td></tr> <tr> <td>2</td><td>RFU</td><td>0</td></tr> <tr> <td>3</td><td>RFU</td><td>0</td></tr> <tr> <td>4</td><td>RFU</td><td>0</td></tr> <tr> <td>5</td><td><i>alert_battery_low</i></td><td>0</td></tr> <tr> <td>6</td><td>RFU</td><td>0</td></tr> <tr> <td>7</td><td><i>alert_no_usage</i></td><td>1</td></tr> </tbody> </table>		Bit	Parameter	Example	0	<i>alert_tamper</i>	0	1	RFU	0	2	RFU	0	3	RFU	0	4	RFU	0	5	<i>alert_battery_low</i>	0	6	RFU	0	7	<i>alert_no_usage</i>	1
Bit	Parameter	Example																													
0	<i>alert_tamper</i>	0																													
1	RFU	0																													
2	RFU	0																													
3	RFU	0																													
4	RFU	0																													
5	<i>alert_battery_low</i>	0																													
6	RFU	0																													
7	<i>alert_no_usage</i>	1																													

31	bits8	0x88	<i>manufacturer_specific</i>
Bit	Parameter	Example	
0-2	RFU	b000	
3-7	<i>battery_remaining_semesters</i> (half years)	b10001 = 17	$17 / 2 = 8.5$ (years)

## 3 Annex: Understanding Payload Structures

---

### 3.1 Example Payload Structure

Every Payload structure description comes in following structure: example payload and then table with similar columns.

Example payload from/to fPort 50: 02 4A 10 0E 32

G	Byte	Type	Example	Parameter	Details	Example Value															
	0	uint8	0x02	_packet_type	0x02 - configuration_packet	configuration_packet															
	1	bits8	0x4A	configured_parameters	Example: 0x4A = b0100 10 1 0  <table border="1"> <thead> <tr> <th>Bit</th> <th>Parameter</th> <th>Example</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>secondary_interval_sent</td> <td>0</td> </tr> <tr> <td>1</td> <td>RFU</td> <td>1</td> </tr> <tr> <td>2-3</td> <td>some_2bit_parameter</td> <td>b10 = 2</td> </tr> <tr> <td>4-7</td> <td>some_4bit_parameter</td> <td>b0100 = 4</td> </tr> </tbody> </table>	Bit	Parameter	Example	0	secondary_interval_sent	0	1	RFU	1	2-3	some_2bit_parameter	b10 = 2	4-7	some_4bit_parameter	b0100 = 4	
Bit	Parameter	Example																			
0	secondary_interval_sent	0																			
1	RFU	1																			
2-3	some_2bit_parameter	b10 = 2																			
4-7	some_4bit_parameter	b0100 = 4																			
	2	int16	0x10	main_interval_s	converter: *2	0x0E 10 = 3600 * 2 = 7200 (s)															
	3		0x0E																		
	r0	uint8	0x32	secondary_interval	when: configured_parameters:secondary_interval_sent 0xFF - not_configured	0x32 = 50															

The payloads are described in top to bottom structure. Bitwise least significant bit comes first (lsb), bytewise least significant byte comes first (LSB).

Human readability of hex arrays introduces confusion into this. E.g. decimal value of 1000000 in hexadecimal is 0x000F4240 (LSB on the right) but in hexadecimal payload string it is usually printed LSB on the left 40 42 0F 00 .

Example payload hex has LSB on the left. Different parameter portions in hex are separated with whitespace. Packet fPort and direction (in reference to NAS module) are also signified with to (downlink) and from (uplink).

### 3.2 Payload Structure Columns Explanation

Column: G

Optional group column to help to identify which blocks are inseparable.

Column: Byte

Byte column expresses byte position. Always starting with 0 due to array first member being 0. The sequence is broken with the start of every optional block. From the first optional block onwards the positions are relative, therefore e.g. r0, r1.

Column: Type

Type column determines encoding and length of the data.

Type	Length in bytes	Encoding
uint8 / int8	1	8 bit unsigned / signed integer
uint16 / int16	2	16 bit unsigned / signed integer
uint32 / int32	4	32 bit unsigned / signed integer
uint64 / int64	8	64 bit unsigned / signed integer
bits8 / bits16	1 / 2	8 bit / 16 bit bitfield (flags and/or decimals)
string	N	N bytes of string (byte array), encoding utf-8

Column: Example

Example bytes to help to understand how bytes from example payload are mapped. Hex values on Example column hex values can be matched top-down with Example payload hex left to right. Grey hex means that this value is constant.

## Column: Parameter

*parameter\_name* is descriptive name of parameter, formatted in *italic\_snake\_case*. They are used consistently throughout the documentation and intended to be used in parsers.

RFU - reserved for future use

*grey\_parameter* - should be hidden in the end parser to declutter the results.

*x\_parameter\_sent* - sent keyword indicates that this bit controls following block denoted like when: *x\_parameter\_sent*.

*main\_interval\_s* - the unit is always behind double underscores '\_\_\_\_'. Unit L/h would be \_\_\_\_L\_h. Unit °C would be \_\_\_\_C.

## Column: Details

*defined\_options* or *special\_values* are italic and indigo blue.

*n/a* - not available / not applicable

Under detailed bitfields tables Bit 0 is 0x01 and Bit 7 is 0x80.

Used Keywords:

when: defines the conditions when the block will be active. When shows the relationships between flags and existence of optional blocks.

converter: defines how to convert the value to extract the intended value by e.g. adding offset or multiplying with something.

formatter: defines how to format the value.

## Column: Example Value

Shows how to convert the Example column's hex into useful output value.