MerryloT Leak Detection

Doc ver.: BQW_03_0038.006





Features

- Compliance to LoRaWAN1.0.3
- Built-in water-sensing probes
- · IP67-rated waterproof housing
- Battery-powered (2 standard AA alkaline batteries)
- · Detection for both flood and water dripping
- Built-in alarm buzzer with sound pressure level 80 dB(min)
- · Press-and-play installation
- Support coverage test by pressing test button

The **MerryloT Leak Detection** utilizes LoRaWAN connectivity to sends uplink notification when water dripping, or flood is detected. And with the built-in alarm buzzer, you wouldn't miss the possible flooding.

Specification		
Model Name	WL10	
Frequency	EU 868 MHz US 902~928 MHz	
Antenna Gain	-2dBi Peak	
RF Sensitivity	-135dBm	
Battery Type	1.5 V AA Alkaline x 2 pcs, 5400 mAh (75ΩCont. discharge)	
Battery Lifetime*	About 3 years. *Note: Battery life is mainly determined by the reporting frequency. Other factors include moisture and high temperature.	
Average Current	135 mA maximum / 100 uA minimum	
Protocol	LoRaWAN 1.0.3	
Operation Temperature	0 to 50°C	
Environmental Rating	IP67 equivalent	
Dimensions	70 mm x 26.5 mm x 70 mm	
Weight	89 g	
Sensor	 Water sensing probes Temperature sensor: Accuracy: ± (1°C) Humidity sensor: Accuracy: ± 5 % Three-axis linear accelerometer 	
Type Approval	CE/FCC/IC approved.	



MerryloT Leak Detection

Doc ver.: BQW_03_0038.006

SKU Detail			
SKU	Country	Frequency Band (MHz)	
WL10-915	USA	US915 (902~928)	
WL10-868	Europe	EU868 (862~870)	

