

LoRaWAN Water Leak Sensor





OVERVIEW:

The Dragino LWL04 is a LoRaWAN Water Leak Sensor. When there is water between the bottom 3 metal posts, the LWL04 indicates a water leak event and uplink to IoT server via LoRaWAN network.

The Dragino LWL04 does not need to be fixed, only placed on the ground. The bottom three metal columns can adjust the height. Only when there is water between the three metal columns, it will cause a short circuit alarm.

LWL04 can be activated from the bottom of the housing with a magnet, and the light will indicate when the magnet is close. Its main unit has a sealing ring, which can achieve IP65 waterproof.

LWL04 is powered by CR123A non-rechargeable battery and target for long time use, these batteries can provide about 16,000 ~ 70,000 uplink packets, which result in 2 ~ 10 years battery life. After battery running out, user can easily open the enclosure and replace with CR123A batteries.

The LWL04 will send periodically data every day as well as for each water leak event. It also counts the water leak times and calculate last water leak duration. User can also disable the uplink for each water leak event, instead, device can count each event and uplink periodically.

Each LWL04 is pre-load with a set of unique keys for LoRaWAN registration, register these keys to LoRaWAN server and it will auto connect after power on.

Features:

- LoRaWAN v1.0.3 Class A
- Water Leak detect
- IP65 waterproof
- CR123A 1500mAh batteries
- Downlink to change configure
- AT Commands to change parameters
- Support wireless OTA update firmware
- Uplink on periodically and water leak event
- Bands: CN470/EU433/KR920/US915/EU868/AS923/AU915/IN865/RU864

Dragino Technology Co., Limited

Room 202, Block B, BCT Incubation Bases (BaoChengTai), No.8 CaiYunRoad LongCheng Street, LongGang District ; Shenzhen 518116,China Direct: +86 755 86610829 | Fax: +86 755 86647123

Applications:

- Smart Factory
- Smart Buildings & Home Automation

Order Info: LWL04-XXX

XXX: The default frequency band

 XXX: Frequency Bands, options: EU433, CN470, EU868, IN865, KR920, AS923, AU915, US915

WWW.DRAGINO.COM sales@dragino.com



Water Leak Installation Environments





Washing Room

Store



Kitchen



Heating

Dragino Technology Co., Limited

Room 202, Block B, BCT Incubation Bases (BaoChengTai), No.8 CaiYunRoad LongCheng Street, LongGang District ; Shenzhen 518116,China Direct: +86 755 86610829 |Fax: +86 755 86647123 WWW.DRAGINO.COM sales@dragino.com