

Wall Switch

Featuring LoRaWAN®

WS50x

The Milesight logo features a stylized blue 'M' followed by the word 'Milesight' in a black, italicized sans-serif font.

WS50x is a smart LoRaWAN® wall switch for the local and remote control of lights and electrical appliances. It adopts two standard sizes for most of international wall switch types, which can replace the traditional wall switches directly. Compliant with Milesight LoRaWAN® gateway and Milesight IoT Cloud solution, WS50x can be monitored and controlled via webpage or mobile App remotely and triggered by other Milesight sensors.

WS50x can be widely used for indoor applications in homes, offices, hotels, museums, etc.

◆ Features

- Support local or remote control via high reliability relay
- Collect current, voltage, power, electrical consumption and support overload protection
- Built-in switch indicator, easy to use in dark environment
- Ultra-wide-distance wireless transmission up to line of sight of 15 km
- Equipped with NFC for one touch configuration and support card emulation mode
- Function well with standard LoRaWAN® gateways and network servers
- Compliant with Milesight IoT Cloud
- Support Milesight LoRa D2D protocol to enable ultra-low latency control without gateway
- Support multicast feature to control switches in bulk

◆ Specifications

Wireless Transmission	
Technology	LoRaWAN [®] , LoRa D2D
Frequency	CN470/IN865/RU864/EU868/US915/AU915/KR920/AS923-1&2&3&4
Tx Power	16 dBm (868 MHz)/22 dBm (915 MHz)/19 dBm (470 MHz)
Sensitivity	-137dBm
Mode	OTAA/ABP Class C
Electrical	
Switches	1-Gang/2-Gang (Optional)
Switch Indicator	Ice Blue
Input Voltage	100~250 VAC, 50~60 Hz
Maximum Current	Inductive: 5 A per Gang, Total 10 A Resistive: 10 A per Gang, Total 10 A
Rated Load	Max 1000 W per Gang, Total 2000 W
Terminal	SPST
Circuit Type	3-Wire
Measurement	Voltage (VAC), Current (mA), Power Factor (%), Power (W), Power Consumption (kWh)
Software	
Configuration	NFC
Switch Control	Local Press or Remote Control
Advanced Features	Schedule Switch, Switch Lock, Overcurrent Protection, Multicast, LoRa D2D Controller, LoRa D2D Agent
Physical Characteristics	
Ingress Protection	IP20
Material	Antiflaming Polycarbonate
Color	White (Customizable)
Dimensions	86 Type: 86 × 86 × 40 mm (3.39 × 3.39 × 1.57 in) 120 Type: 118 × 72 × 46.9 mm (4.65 × 2.83 × 1.85 in)
Operating Temperature	-20°C to +60°C (-4°F to +140°F)
Relative Humidity	0% to 95% (non-condensing)

